

# HIGH PRESSURE FOGGING PUMPS

## Standard Pulley Driven Pumps

### 800 PSI

Part #	Flow	HP	Power	Dimension/Weight
61025	1.0 GPM	1.0	115/208-230 12.8/6.4 amp	24L x 14W x 12H 80 lbs
61050	1.5 GPM	1.5	115/208-230 17.2/8.6 amp	24L x 14W x 12H 85 lbs

- All pumps are standard single phase 60 hz
- Three phase motors available - 230/460v
- Available with 50hz power supply for international applications
- 1 year warranty

## STANDARD FEATURES

- Triplex plunger pump
- Produces up to 800 psi from line pressure
- Pulley driven
- Totally enclosed
- Weather resistant
- 5-micron sediment filter
- Low RPM
- Low noise level
- Liquid filled pressure gauge
- Solenoid valve
- Adjustable unloader valve
- Voltage 115/208-230 60HZ

## Commercial Pulley Driven Pumps

Part #	Flow	HP	Power	Dimension/Weight
71025	1.0 GPM	1.5	115/208-230 17.2/8.6 amp	30L x 17W x 14H 115 lbs
71050	1.5 GPM	1.5	115/208-230 17.2/8.6 amp	30L x 17W x 14H 115 lbs
71075	2.4 GPM	2	115/208-230 19.0/10.5 amp	30L x 17W x 14H 120 lbs
71100	3.2 GPM	3	208-230 33.8/16.8 amp	30L x 17W x 14H 150 lbs
71125	4.0 GPM	3	208-230 33.8/16.8 amp	30L x 17W x 14H 150 lbs
71150	4.8 GPM	5	208-230 23.2 amp	30L x 17W x 14H 160 lbs

- All pumps are standard single phase 60 hz
- Three phase motors available - 230/460v
- Custom pumps for international applications also available
- 3 year warranty

## What pump size do I need?

To determine pump size refer to nozzle flow chart on page 14. Call our High Pressure Technical Support Center for more information. If you need 5 nozzles or 500, we have the pump to meet your requirements.



Pool by California Pools

