

HIGH PRESSURE KITS

High Pressure Kits

KITS INCLUDE

- Corresponding size pump module
- Number of Slip Lok nozzle assemblies
- Number of 28"(71cm) sections of nylon tubing
- 50'(15m) roll of nylon tubing
- End Plug
- 90° Slip Lok elbows
- 2 automatic drain valves
- 3-way tee
- Tubing cutter
- 5-micron sediment filter assembly
- 8 oz. bottle of nozzle cleaner
- 3/8" stainless steel clamps
- Installation & Instruction Manual included

Part #	Pump Type	# of nozzles
80015	1/2hp direct drive pump	15
80025	1hp direct drive pump	25
80050	1.5hp direct drive pump	50
80200	5hp direct drive pump	200
80250	5hp direct drive pump	250
60025	1hp pulley drive pump	25
60050	1.5hp pulley drive pump	50

The Following commercial pumps have a 3 year warranty.

70025	1.5hp pulley drive pump	25
70050	1.5hp pulley drive pump	50
70075	2hp pulley drive pump	75
70100	3hp pulley drive pump	100
70125	3hp pulley drive pump	125
70150	5hp pulley drive pump	150

- Specify voltage requirements when ordering



CUSTOM HIGH PRESSURE KITS AVAILABLE

Our kits utilize patented Slip Lok fittings and 3/8" semi-rigid nylon tubing and are designed as a do-it-yourself project requiring no previous fogging installation experience.

60025 25 Nozzle Kit 58.5 ft. (18 meters)

Installation & Instruction Manual included

Part #	Qty	Description
61025	1	1 GPM pulley driven pump
41010	1	Filter cartridge
41002	1	Filter housing with bracket
42004	25	Nylon tubing 28" pre-cut lengths
42002	1	50 ft. Coil nylon tubing
12109	25	HP Slip Lok T without nozzle
90192	30	.012 orifice brass & stainless nozzle
10409	75	3/8" stainless steel clamp
12114	4	3/8" Slip Lok 90° elbow
12115	2	3/8" Slip Lok three way T
12122	1	Slip Lok hose adapter
12119	1	End plug
91001	2	Auto drain valve
42006	10 feet	Low pressure tubing
92410	1	Tubing cutter
92201	1	8 oz. nozzle cleaner
12106	2	3/8" x 1/2" male adapter

60050 50 Nozzle Kit 116 ft. (35.5 meters)

Installation & Instruction Manual included

Part #	Qty	Description
61050	1	1.5 GPM pulley driven pump
41010	1	Filter cartridge
41002	1	Filter housing with bracket
42004	50	Nylon tubing 28" pre-cut lengths
42002	1	50 ft. Coil nylon tubing
12109	50	HP Slip Lok T without nozzle
90102	55	.012 orifice brass & stainless nozzle
10409	125	3/8" stainless steel clamp
12114	4	3/8" Slip Lok 90° elbow
12115	2	3/8" Slip Lok three-way T
12122	1	Slip Lok hose adapter
12119	1	End plug
91001	2	Auto drain valve
42006	10 feet	Low pressure tubing
92410	1	Tubing cutter
92201	1	8 oz. nozzle cleaner
12106	2	3/8" x 1/2" male adapter



Contact our High Pressure Technical Support Center for all the details on this innovative approach to high pressure fogging.