

# DIRECT DRIVE & MEDIUM PRESSURE PUMPS

## Direct Drive Pumps

### 800 PSI

Part #	Flow	Power	Dimension/Weight
81015	.5 GPM	115/208-230 8.8/4.6 amp	21L x 9W x 9H 45 lbs
81025	1.0 GPM	115/208-230 12.8/6.4 amp	26L x 16W x 9H 55 lbs
81050	1.5 GPM	115/208-230 17.2/8.6 amp	26L x 16W x 9H 65 lbs
81200	6.3 GPM	208-230 23.2 amp	26L x 15W x 9H 115 lbs
81250	7.9 GPM	208-230 23.2 amp	24L x 16W x 9H 120 lbs

#### PUMP FEATURES

- Adjustable unloader valve
- Glycerin-filled gauge
- 5-micron sediment filter assembly
- Solenoid valve
- 8 foot power cord w/ plug
- All pumps standard single phase 60 hertz
- Three phase available - 230/460 volt
- Custom pumps for international applications also available
- One year warranty



## Medium Pressure Pumps

### 250 PSI

#### DOMESTIC AND INTERNATIONAL

Part #	Flow	HP	Power	Dimension/Weight
51015	60 GPH	1/2	115/208-230 7.8/3.9 amp	16L x 10W x 8H 25 lbs

#### STANDARD FEATURES

- 1/2 HP Motor 50/60hz 115 volts
- 1725 RPM
- Up to 25 nozzles
- 60 GPH/250 psi
- 6' cord w/ plug
- Totally enclosed cover
- Quiet operation
- Weight 25lbs./11kg

#### DOES YOUR MIST SYSTEM NEED A BOOST?

These modules are designed to operate with our standard poly tubing and Slip Lok fittings. The pumps can operate up to 250 psi with flow rates up to 90 GPH. The pumps come standard with electric solenoid valve on the water inlet side of the pump. For customized pump requirements, call our high pressure technical support center.



Provide extended seating to restaurant patios & outdoor waiting areas during hot summer days and nights.