


# ACCESSORIES



## 40601 Thermal Relief Valve

Protects your pump against damaging heat if pump is left in bypass for extended periods.

- Mounts on pump bypass loop
- 1/4" MNPT inlet port
- 1/8" FNPT bleed port
- Relief Temp 145° F
- RTP composite



## 40512 Low Pressure Solenoid Valve

Low pressure water applications

- Normally closed
- Maximum 150 PSI
- Coil continuous duty molded F class
- Brass body 1/2" FNPT
- Standard voltages:  
24, 120, 240, 480 volts  
AC, 60hz (or 110, 220V, AC, 50hz)



## 40504 High Pressure Solenoid Valve

Ideal for multiple zones and automatic control

- Normally open
- 800 PSI working pressure
- Coil continuous duty molded class F
- Brass body 1/4" FNPT
- Standard voltages:  
24, 120, 240, 480 volts  
AC, 60hz (or 110, 220V, AC, 50hz)




## 18012 Low Water Safety Switch

- 3/8" MNPT inlet/outlet
- Rugged inline flow switch
- Flowrate setting: 0.25 GPM to 1.5 GPM
- 115/230 volt



## 92301 Adjustable Chemical Injector

- 3/8" MNPT inlet/outlet
- Up to 10 GPM
- Easy to install, low maintenance
- Built-in bypass
- Mixing ratio up to 5%
- Maximum pressure 85 PSI



## 40101 Pressure Regulator

- Accurate and reliable at all flow rates
- 3/4" inlet x 3/4" MGH outlet
- Outlet pressure 45 PSI
- Chemical resistance



## Brass Ball Valves

Designed for use with water. Forged brass body, chrome plated ball and stem, full flow ports, and O-ring sealed stem

Part No.	Port Size
40303	1/4" x 1/4" FNPT
40307	3/8" x 3/8" FNPT
40308	1/2" x 1/2" FNPT
40309	3/4" x 3/4" FNPT
40305	1/4" sweat
40306	1/2" sweat

- Rated pressure 600 PSI
- Maximum temp. 195° F
- Teflon seats



## 40304 Stainless Steel Ball Valve

Two piece all stainless steel valve. ANSI 316SS ball, stem and body 1000 PSI. WOG valve can be locked in either open or closed position. Flows in either direction


- 1/4" x 1/4" FNPT Port Size



## 40001 Unloader Valve

Brass body construction with stainless steel valve ball and seat. 3/8" FNPT inlet, 3/8" FNPT discharge and 3/8" FNPT bypass.

- Maximum flow 7.8 GPM
- Maximum PSI 2900
- Maximum temp. 195° F



## Nozzle Cleaner

**Part No. Description**

92201	8 oz.
92202	1 gallon

- Calcium & scale remover
- Non-toxic
- Bio-degradable



## 92003 Pulse Hose 40"

- Reduces line vibration
- 3/8" MNPT
- Installs on discharge line

